

Computing Quasibrittle Failure Probability: from Nano to Macro

Zdeněk P. Bažant

McCormick Institute Professor and W.P. Murphy Professor
of Civil Engineering and Materials Science,
2145 Sheridan Road, CEE, Northwestern University, Evanston, Illinois 60208, USA
z-bazant@northwestern.edu

Abstract: In civil, aeronautical and naval engineering, in protection from natural hazards, and in micro-electronics and MEMS, and one must ensure an extremely small failure probability, $< 10^{-6}$. How to do that is adequately understood only for the limiting special cases of perfectly brittle or ductile behaviors, for which the structural strength distribution is necessarily Weibullian or Gaussian, respectively. Presented is a computational approach to do that for the broad class of quasibrittle structures, which have brittle constituents with material inhomogeneities of non-negligible size, and include structures made of concrete (as the archetypical case), rocks, fiber composites, wood, toughened ceramics, rigid foams, sea ice, stiff soils, snow slabs, etc., as well as metals and ceramics on approach to nano-scale. It is shown that, for such structures, the strength distribution is transitional, having a Weibull asymptote (with zero threshold) on the left and a Gaussian (normal) asymptote on the right, with the transition center shifting from left to right as a function of structure size and geometry. The consequence is that, for quasibrittle structures, the understrength partial safety factor must also be computed as a function of size and geometry. Computing merely the mean and standard deviation of structural strength is insufficient, while a purely computational evaluation of the far-out distribution tail for any given structure size and geometry is beyond reach. Therefore, computational mechanics must be combined with a physically based model of the distribution, to anchor the tail to the mean and standard deviation, both of which can be computed easily, e.g., by combining finite elements or discrete elements with Latin hypercube sampling. It is shown how the transitional distribution of strength of a representative volume element (RVE) of material can be derived from the interatomic potential, Maxwell-Boltzmann distribution of atomic energies and stress dependence of the activation energy, how (for failures occurring at crack initiation) the RVE distribution can be scaled up with structure size, considering its geometry, and how asymptotic matching techniques can overcome computational challenges. Using Morse interatomic potential, the theory is further extended to predict the distribution of lifetime of quasibrittle structures and show how it depends on structure size and geometry. The theory is verified by comparisons with experimental strength histograms and size effect tests of concrete, ceramics and fiber composites. Finally, as an example, it is shown that the tolerable abutment displacement of the Malpasset dam, catastrophically breached in 1959, would today have to be about 4-times smaller than assumed at the time of design.

References:

1. Bažant, Z.P. (2004). "Scaling theory for quasibrittle structural failure." Proc., National Academy of Sciences 101 (37), 13397-13399.
2. Bažant, Z.P., and Pang, S.-D. (2007). "Activation energy based extreme value statistics and size effect in brittle and quasibrittle fracture". J. of the Mechanics and Physics of Solids 55, 91-134.
3. Bažant, Z.P. (2004). "Probability distribution of energetic-statistical size effect in quasibrittle fracture." Probabilistic Engineering Mechanics 19 (4), 307-319

4. Bažant, Z.P. (2002). "Scaling of Structural Strength". Hermes Penton Science, London (Errata: www.civil.northwestern.edu/people/bazant.html); 2nd updated ed. Elsevier 2005.
5. Bažant, Z.P., and Planas, J. (1998). "Fracture and Size Effect in Concrete and Other Quasibrittle Materials". CRC Press, Boca Raton and London.
6. Bažant, Z.P., Vořechovský, M., and Novák, D. (2007). "Asymptotic prediction of energetic-statistical size effect from deterministic finite element solutions." J. of Engrg. Mechanics ASCE 128, 153-162.
7. Bažant, Z.P., Vořechovský, M., and Novák, D. (2007). "Energetic-Statistical Size Effect Simulated by SFEM with Stratified Sampling and Crack Band Model." Int. J. of Numerical Methods in Engineering, 71, 1297-1320.
8. Bažant, Z.P. (2007). "Mechanics based prediction of structure size and geometry effects on safety factors for composites and other quasibrittle materials." Proc., 48th AIAA/ASME/ASCE/AHS/ASE Structures, Structural Dynamics and Materials Conference, Honolulu, Hawaii, pp. 1-15.